

MODEL		SL-2AA	SL-3AA	SL-5AA	SL-8AA	SL-10AA	SL-12AA	SL-15AA	SL-20AA	SL-30AA	SL-40AA	SL-50AA	SL-60AA	
SOĞUTMA KAPASİTESİ REFRIGERATION CAPACITY	kW	5	10	15	20	30	40	45	60	90	120	150	180	
	kcal/h	5160	7740	12900	20640	25800	30960	38700	51600	77400	103200	129000	154800	
KOMPRESÖR GİRİŞ GÜCÜ COMPRESSOR INPUT POWER	HP	2	3	5	8	10	12	15	20	30	40	50	60	
SOĞUTUCU DOLUM MİKTARI REFRIGERANT FILLING QUANTITY	TİP	R22												
	KG	1.4	1.5	2.5	3.5	5	6	7.5	10	12	18	30	35	
SU TANKI WATER TANK	L	40	60	90	120	180	135	270	350	-	-	-	-	
BUHARLAŞMA EVAPORATOR	TİP	SERPANTİN BORU TİPİ / SERPANTINE PIPE TYPE								KABUK TİPİ / SHELL TYPE				
FREEZING WATER PIPE		1"	1"	1"	1"	1.5"	1.5"	2"	2"	3"	3"	3"	4"	
SOĞUTMA SUYU AKIŞI FREEZING WATER FLOW RATE	L/min	60	60	90	90	210	210	270	315					
	m3/h	3.6	3.6	5.4	5.4	11	11	16	16	16	23	28	33	
FAN MOTORU GÜCÜ FAN MOTOR POWER	kW	EKSENEL AKIŞ TİPİ HAVA FANI / AXIAL FLOW TYPE BLOWER FAN												
		0.13	0.45	0.45	1.5	0.45x2	1.5	0.65x2	0.65x2	0.65x4	0.65x4	1.1x2	1.8x4	
KORUMA SAFETY PROTECTION		YÜKSEK VE ALÇAK BASINÇ KOMPRESÖR AŞIRI YÜK, POMPA AŞIRI YÜK KORUMASI PROTECTION OF HIGH&LOW PRESSURE, COMPRESSOR OVERLOAD, PUMP OVERLOAD						YÜKSEK VE ALÇAK BASINÇ KOMPRESÖR AŞIRI YÜK, POMPA AŞIRI YÜK, DONMA, AKIŞ HIZI KORUMASI PROTECTION OF HIGH&LOW PRESSURE, COMPRESSOR OVERLOAD, PUMP OVERLOAD, ANTIFREEZING, FLOW RATE						
GÜÇ POWER		AC3+N+PE 50/60HZ												
DIŞ ÖLÇÜLER EXTERNAL DIMENSIONS	U (L)	770	750	1100	1480	1450	1640	2200	2200	2200	2500	2200	3000	
	G (W)	580	680	680	840	790	940	1000	1320	1320	1200	2000	2200	
	Y (H)	1115	900	1100	1435	1120	1520	2100	2100	2180	2290	2180	2180	
AĞIRLIK WEIGHT	KG	200	100	160	200	300	500	700	750	1400	1600	2200	2400	